

VISTA HI-LITE FLAT SCREEN MONITOR



HI-RESOLUTION HI-PERFORMANCE

The stylish new Vista HI-LITE flat screen monitor combines high-performance with affordability. Its 17" screen combines 650TVL resolution, a fast 5mS refresh time, and 1000:1 contrast ratio to provide a crystal-clear display for either CCTV or PC imagery. In addition to an advanced 3D comb filter to improve sharpness, the HI-LITE produces exceptional image quality at a very competitive price.

Ideal for all applications where display functionality is combined with modern aesthetics such as retail outlets or offices, the Vista HI-LITE is equally at home in CCTV control rooms or industrial premises, thanks to the increased screen protection offered by its optically correct glass fronted panel.

Flexibility of input choice (2 BNC, SVHS, DVI/VGA and audio), and simple on screen display (OSD) set-up affords easy installation, selectable via a multi-lingual menu. The Vista HI-LITE monitor can also be wall or desk mounted via an integral 100mm Vesa mount option.

To learn more about this product range please visit us at vista-cctv.com



Key Features:

Hi Resolution panel

650TVL panel gives great detail in the picture content

Glass front panel

Affords extra protection and optically correct viewing

Excellent picture quality

The inclusion of a 3D comb filter, combined with 5mS response and 1000:1 contrast results in a very high quality picture

Simple set-up

Intuitive menu operation means easy operation

Multiple inputs

2 BNC, SVHS, DVI/VGA and Audio inputs allow CCTV or PC imagery to be displayed

Multi-lingual display

Affords easy set-up in multiple languages

THE PROFESSIONAL CHOICE

MODELS IN THIS RANGE

HI-LITE 17 inch Glass fronted hi-res TFT monitor

TECHNICAL SPECIFICATION

INPUTS

Video (PAL/NTSC) 2 off looping BNCs (Level 1.0Vp-p/75 ohm)
1 off S-Video 4 pin mini-din (Level 1.0Vp-p/75 ohm)

Video Special 3D Comb filter, 3D Video De-interlaced, DNR

PC DVI-I (Digital and Analogue)
VGA / SVGA / XGA / SXGA
FH: 31.5-80KHz FV:56-75HZ

Audio 2 off Phono jack (level 1.0Vp-p/1Khz)
2 off internal speakers (1W)

PANEL

Type 17 inch TFT colour LCD

Resolution 650TVL

Screen size 431mm diagonal

Viewable size 337.9mm (H) 270.3mm (V)

Dot Pitch 0.264mm x 0.264mm

Viewable angle 80/80/80/80 degrees

Contrast ratio 1000:1

Brightness 300cd/m2

Resolution 1280 x 1024

Colour display 16.7M

Response time 5ms

ELECTRICAL

Power Input 12Vdc input via external 100-240Vac Adaptor

Power Consumption 40W

PHYSICAL

Dimensions 372 X 359 x 190 (unpackaged)
424 x 441 x 164 (packaged)

Weight 4.07Kg (Net) 5.57kg (Gross)

User controls Channel/+/-/Menu/Power

Special features Key Lock
Running Hours log
Picture freeze
Fast switching time
Vivid mode

ACCESSORIES

Power leads, DVI to D-Sub cable, Stereo audio cable

Optional brackets Wall mount, pole mount

REGULATIONS

CE, RoHS, FCC

ASSOCIATED PRODUCTS

Spare PSU VFSMPSU



No liability will be accepted by Vista for any errors or omissions in this information.

DS-HI-LITE-version1