



VISTA PROTOS^{IV}

STANDARD TRUE DAY/NIGHT RANGE



VISTA PROTOS - EUROPE'S FAVOURITE CAMERA

With a completely new look and feel across the entire range, Protos^{IV} cameras are amongst the most stylish and technically proven cameras for internal and external installations available today, regardless of the intended application or surrounding lighting conditions.

The result of a painstaking research and development program, these cameras offer a stunning array of complimentary features, including an innovative high-resolution 540TVL CCD capable of producing razor sharp evidential quality images.

Protos^{IV} day/night cameras provide true IR filter switching for use with IR lights ensuring effective 24 hour operation. Benefiting from a user selectable "hi/low" mode the camera can switch to a monochrome operation at different lighting levels. An external contact input is also provided for manual/mechanical override.

IDEAL FOR APPLICATIONS SUCH AS:

- Town centres
- Retail
- Office blocks
- Schools
- Warehouses
- Military
- Ports & airports
- Rail & roadways
- Residential

MAIN FEATURES:

- 1/3" versions
- True 540TVL colour & 330TVL options
- 0.08 lux sensitivity
- Moving IR filter for use with IR lamps
- Dual level switching mode to day/night operation
- External contact to switch from day/night operation
- BLC on/off
- AGC on/off
- AI/DD single auto sensing socket
- Easy back-focus via thumb wheel
- 98-260V AC or 11 - 40V DC / 12 - 30V AC



THE UK'S PREMIER CCTV BRAND



TECHNICAL SPECIFICATION

	VPC032/DN VPC030/DN	VPC132/DN VPC130/DN
SENSOR (CCD)	1/3"	
RESOLUTION (SUPER HAD)	330/380TVL	540/580TVL
SENSITIVITY	0.6/0.08 lux @ F1.2	0.7/0.1 lux @ F1.2
DAY/NIGHT	Auto (hi/low mode) & Ext cont.	
SIGNAL / NOISE RATIO	>50dB AGC Off	
SYNC. SYSTEM	INT/line lock	
BACK LIGHT COMP	On/off Selectable	
IRIS MODE	Video / Direct (auto sensing) / ESC selectable	
SHUTTER SPEED	Auto - 1/50 - 1/100,000	
GAMMA	0.45	
AGC	AGC On/off	
AWB	Yes	
AMBIENT TEMP	-10°C + 50°C	
DIMENSIONS	132 x 65 x 62mm	
WEIGHT	425g	
VOLTAGE	11 - 40V DC / 12 - 30V AC 98 - 260V AC < 6W	

ORDERING INFORMATION

VPC032/DN	1/3", 330TVL, 0.6/0.08 LUX TRUE DAY/NIGHT CAMERA, 11-40V DC/12-30V AC
VPC030/DN	1/3", 330TVL, 0.6/0.08 LUX TRUE DAY/NIGHT CAMERA, 98-260V AC
VPC132/DN	1/3", 540TVL, 0.7/0.1 LUX TRUE DAY/NIGHT CAMERA, 11-40V DC/12-30V AC
VPC130/DN	1/3", 540TVL, 0.7/0.1 LUX TRUE DAY/NIGHT CAMERA, 98-260V AC

ASSOCIATED PRODUCTS



Varifocal lenses VDD35V814Pe, VDD5V5014Pe and VDD20V10014P etc.
VDD45V1212Pe, VDD6V1214P
IR Corrected lenses VDD3V811RP, VDD28V1111RP, VDD10V40141RP and VDD4V12121RP etc.



12V DC PSU's VPSU500/12 & VPSU1000/12
24V AC PSU's VPSU24VAC/750, VPSU24VAC/2000 & VPSU24VAC/4000



Wall brackets VCMB, Protos B1, Protos B2 etc.



External housings VCMHF, VSCMHF & VLHE300W

DISTRIBUTED BY:

ALL SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE



VISTA NORBAIN HOUSE, ESKDALE ROAD, WINNERSH TRIANGLE, WOKINGHAM, BERKSHIRE. RG41 5TS
TELEPHONE: +44 (0) 118 944 0123 FAX: +44 (0) 118 944 0999
WEBSITE: WWW.VISTA-CCTV.COM